HOLDEN FIRE DEPARTMENT

ALL SMOKE DETECTORS MUST BE CEILING MOUNTED

		Year built or Substantially Modified				
		Before 1975	1975 - 8/27/97	8/27/97 - 2007	1/08 - 8/10	8/10 - Present
Sı	noke Detector Powered by:					
	Battery Operated	Allowed	Not Allowed	Not Allowed	Not Allowed	Not Allowed
	Hardwired, Interconnected	Allowed	Required	Not Allowed	Not Allowed	Not Allowed
	Hardwired, Interconnected w/battery backup	Recommended	Recommended	Required	Required	Required

Type of Smoke Detector:							
		Outside 20 FT, of kitchen or full bathroom					Photoelectric OR Dual Detector*
		Within 20 FT. of kitchen or full bathroom	Photoelectric	Photoelectric OR Ionization	Photoelectric	Photoelectric	Photoelectric

	, , , , , , , , , , , , , , , , , , ,	MUST BE IN THE HALLWAY OUTSIDE THE SLEEPING AREA, WITHIN 10 FEET OF EACH BEDROOM DOOR				
Γ	Battery OR Plug-in w/battery backup	Allowed	Allowed	Allowed	Not Allowed	Not Allowed
Γ	Hardwired, interconnected w/battery backup	Allowed	Allowed	Allowed	Required	Required

Locations required:						
	Finished or Habitable Basement	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
	Every Habitable Level	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
	Base of Stairs	Smoke	Smoke	Smoke	Smoke	Smoke
	Outside each Sleeping Area (hallway)	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
	Inside every Bedroom	Not Required	Not Required	Smoke	Smoke	Smoke
	Finished Attic (Habitable)	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
	Garage (Attached)	Not Required	Not Required	Not Required	Heat Detector	Heat Detector

ation technology

> Low Volatage fire warning systems are exempt from the dual technology requirement

This is a guide only. Please call Fire Prevention if you should still have questions: 508-210-5650

> Combination Smoke and Carbon Monoxide Alarms MUST have a Voice Feature

> SMOKE DETECTORS 10 YEARS FROM DATE OF MANUFACTURE NEED TO BE REPLACED PER MA FIRE CODE